



Material:

- Handle: Glass fibre reinforced polyamide (PA6GF30), black.
- Torx T-30 screw: Steel, zinc plated.

References, Accessories:

- Keys: Page 2-370 and 2-372.

Notes, Tests:

Inside handle may only be used in combination with non-locking outside handle.

Red handles available on request.

With these handles can your Klima-flex 1 (K1) latching unit be equipped with the next generation Klima-flex 2 (K2) handles. A large supply of handle combinations are available - tool operated, key locking, pad-locking and non-locking, depending on your application. System Klima-flex for HVAC applications is designed for extreme simplicity in mounting in your insulated (double skinned) door application. Handles may be used on either inside or outside of the door.

Key extraction: Open / closed.

Products marked with * are key-locking and are supplied with two keys.

K2 Handles for K1 Latching Units

P/N	Description	Latching type
2651-215400	Without roller cam	Non-locking
2651-215505	Without roller cam	Square 8
2651-215514	Without roller cam	Triangle 7
2651-215534	Without roller cam	Recessed hexagon 8 (5/16 inch)
2651-215680	Without roller cam	IL101 *
2651-215681	Without roller cam	IL0333 *
2651-215690	Without roller cam	Keyed to differ *
2651-235700	One-piece handle. Without roller cam	Pad-lockable
2651-235400	One-piece handle. Without roller cam	Non-locking