



Material:

- Rod guide (A): Glass fibre reinforced polyamide (PA6GF30), black.
- Nut: Steel, zinc plated.
- Rod guide (B): Bracket: Steel, zinc plated or stainless steel (304).
- Bushing (C): Glass fibre reinforced polyamide (PA6GF30), black.
- Adapter (D): Zinc die-cast, zinc plated or stainless steel (304).

References, Accessories:

Please refer to rods for latch system Vision Classic: 1-008.52, 1-008.53.

Notes, Tests:

- A is the distance between the inside face of the door and the rod.
- Rod bushing (C) for other applications or rod guides.
- Rod adapter (D) for rod type R, adds 14 mm to the total length.

Version A

Rod guide with cast-in M6-nut, for round Ø 8 mm rod. For weld-on stud or screw. The opening allows the flat end through the rod guide.

Version B

Rod guide supplied with Polyamide bushing, for low friction and silent movement of the rod. For screw-on or weld-on mounting.

Rod bushing (C) for other applications or rod guides.

Rod adapter (D) for rod type R, adds 14 mm to the total length.

Rod Guides and Accessories - System VISION Classic

P/N	Description	Material	Spec.	For rod type	Drawing
285023	Rod guide	PA6	A=26	All	A
285024	Rod guide	PA6	A=20	All	A
282123	Rod guide	Steel	A=16	P, R, S-L	B
283023	Rod guide	SS (304)	A=16	P, R, S-L	B
282124	Rod guide	Steel	A=22	P, R, S-L	B
283024	Rod guide	SS (304)	A=22	P, R, S-L	B
28212302	Bushing Ø 8 mm	PA6	Cut-out Ø 11 mm	P, R, S-L	C
282119	Rod adapter	Zinc	Ø 8 mm	R	D
283019	Rod adapter	SS (304)	Ø 8 mm	R	D