



Material:

- Handle and dish: Glass fibre reinforced polyamide (PA6GF30), black or zinc, die-cast, black texture powder coated.
- Dust cover: TPE.
- Pivot shaft: Zinc die-cast, zinc plated.

References, Accessories:

- Stainless version: Page 6-010.
- Profile cylinders: Page 1-209a/b, 1-211, 1-210.
- Rod Latch Systems: Page 1-008.00 to 1-008.57.

Notes, Tests:

Cut-out, version C: Page 1-001.01.

Low profile swing handle for 40 mm or 45 mm profile cylinder and control mechanism.

MODEL: Turn-to-latch = The door is locked by turning the key.

T = For door thickness: 0,8-3,5 mm.

PDL = Spring loaded padlock loop retracts when handle is released.

VISION Swing Handle for 40 mm Profile Cylinder (AAAAAAABC-DDDD)

| AAAAAAA | Material | B | T= | C | PDL | -DDDD | Dust cover |
|---------|-------------------------------|---|---------|---|-----|-------|------------|
| 1216118 | Handle zinc / Dish PA6. X=28 | 1 | 0,8-1,5 | 0 | No | -C60U | No |
| 1216418 | Handle zinc / Dish zinc. X=28 | 2 | 1,6-2,5 | | | -C60D | Yes |
| 1250118 | Handle PA6 / Dish PA6. X=28 | 3 | 2,6-3,5 | | | | |

VISION Swing Handle for 45 mm Profile Cylinder (AAAAAAABC-DDDD)

| AAAAAAA | Material | B | T= | C | PDL | -DDDD | Dust cover |
|---------|-------------------------------|---|---------|---|-----|-------|------------|
| 1216118 | Handle zinc / Dish PA6. X=33 | 1 | 0,8-1,5 | 0 | No | -C65U | No |
| 1216418 | Handle zinc / Dish Zinc. X=33 | 2 | 1,6-2,5 | | | -C65D | Yes |
| | | 3 | 2,6-3,5 | | | | |